

# Transport processes-1

## fluid flow

03-02-2022  
Károly Liliom

# Transport = translocation of materials

biological significance: intracellular, intercellular, and transmembrane flow of matter (breathing, blood circulation, transport across membranes, metabolism)





## Distinct transport mechanisms:

- Transport is due to a collective, directional motion of particles, such as in a fluid flow
- Transport is due to independent random motion of particles, such as diffusion
- Transporting materials through lipid bilayers


topics covered in this lecture:

- Transport is due to a collective, directional motion of particles = **A macroscopically observable fluid flow**
- types and laws of flow of fluids and gases
- blood characteristics determining its flow properties

# Macroscopically observable fluid flow



# Flow in rigid-wall tubes



**Volumetric flow rate ( $I_V$ ):**

$$I_V = \frac{\Delta V}{\Delta t} = A \frac{\Delta s}{\Delta t} = A \bar{v}$$


# Stacionary flow

parameters of flow are constant in time

Continuity principle:

**in a stacionary flow the volumetric flow rate is constant**

e.g. law of mass balance for incompressible fluids (gases?)



compressibility:



$$\kappa = -\frac{1}{V} \frac{\Delta V}{\Delta p}$$

$$A_1v_1 = A_2v_2 = \text{constant}$$

$A$  = cross-sectional area

$v$  = flow velocity

# Viscosity – internal friction



- $F$  = shear force
- $A$  = area of fluid layer
- $\eta$  = viscosity
- $v$  = flow velocity
- $y$  = distance between fluid layers
- $F/A$  = shear stress ( $\tau$ )
- $\Delta v/\Delta y$  = velocity gradient ( $D$ )

$$\frac{F}{A} = \eta \frac{\Delta v}{\Delta y} \quad (\text{Newton's friction law})$$

$$\eta = \frac{\tau}{D}$$

Units of viscosity:  $1 \text{ Pas} = 1 \frac{\text{Ns}}{\text{m}^2} = 10 \text{ P} (\text{poise})$

Viscosity of distilled water (25 °C): 1 mPas (1 centipoise)

# Types of flow based on viscosity

## 1. *Ideal*

frictionless, incompressible

$$\rho = \text{constant}, \eta = 0$$


## 2. *Non-ideal (real)*

a. *Newtonian (viscous)*

$\eta$  independent of shear stress

b. *Non-newtonian (anomalous)*

$\eta$  changes with shear stress



$$\eta = \tau / D$$

# Viscosity – internal friction

substance	$\eta$ (mPa·s) 20 °C (101 kPa)
air	0.019
water	1
ethanol	1.2
blood (37 °C)	2–8
glycerine	1490
honey	2000–14000

viscosity of gases increases with rising temperature  $\eta \sim T$


viscosity of fluids decreases with rising temperature

$$\eta \sim e^{\frac{E}{kT}}$$

$$\frac{F}{A} = \eta \frac{\Delta v}{\Delta y}$$

Fluids obeying the above equation are called **newtonian fluids**.

# Friction on spherical particles – Stokes law



Georg Gabriel Stokes  
(1819-1903)

Frictional force is proportional with the velocity:

$$F_s = 6\pi\eta r v$$




$$u = \frac{v}{F} \quad , \quad u = \frac{1}{6\pi\eta r}$$

$u$  is the **mobility** of the sphere, which is the value of the velocity resulting from a unity of force.


# Types of flow:

laminar flow – flow happens in layers, which do not mix

turbulent flow – layers are mixing (chaotic streamlines)



parabolic velocity profile




Osborne Reynolds  
(1842-1912)

Reynolds number (Re):

$$Re = \frac{vr\rho}{\eta}$$

$v$  = flow rate (m/s)  
 $r$  = tube radius (m)  
 $\rho$  = density of fluid (kg/m<sup>3</sup>)  
 $\eta$  = viscosity (Ns/m<sup>2</sup>)



**Re > 1000 – turbulent flow appears**

# Bernoulli's law

conservation of energy in ideal fluids



Daniel Bernoulli  
(1700-1782)

$$p + \frac{1}{2} \rho v^2 + \rho g h = \text{const}$$


$p$  = static pressure

$\frac{1}{2} \rho v^2$  = dynamic pressure


$\rho g h$  = hydrostatic pressure



Giovanni Battista  
Venturi  
(1746-1822)




Static pressure drops at the  
tube narrowing



Applications: sprayer, atomizer, aspirator (vacuum pump), inspirator (Bunsen burner), diffuser, jet engine, wing profile, vacuum cleaner, biphasic pulse in aorta insufficiency

# Hagen-Poiseuille's law

Stationary laminar flow of newtonian fluids and gases in rigid-wall tubes



G.H.L. Hagen  
(1797-1884)



J.-L.-M. Poiseuille  
(1799-1869)

$V$  = volume  
 $t$  = time  
 $R$  = tube radius  
 $\eta$  = viscosity  
 $p$  = pressure  
 $x$  = tube length  
 $V/t = I_V$  = volumetric flow rate  
 $\Delta p/\Delta x$  = pressure gradient, maintained by  $p_2 - p_1$  (negative!)  
 $A$  = cross-sectional area of tube  
 $I_V$  = volumetric flow rate

$$I_V = \frac{V}{t} = -\frac{R^4 \pi \Delta p}{8\eta \Delta x}$$

$$I_V = -\frac{R^4 \pi}{8\eta \Delta x} \Delta p \Rightarrow -\Delta p = R_{tube} \cdot I_V \Rightarrow U = R \cdot I$$


**Ohm's law!**

$$\frac{\Delta v}{\Delta r} \sim r \Rightarrow \left( \frac{\Delta v}{\Delta r} \right)_{\max} = R$$

Shear stress is maximal at the tube wall

# Medical significance of fluid flow laws

Bernoulli's law:



**Formation of aneurysm (pathological expansion of blood vessel):**

- Expansion of vessel: diameter increases
- Flow rate decreases, according to continuity equation
- Static pressure increases due to Bernoulli's law
- Aneurysm pregrebrates - positive feedback mechanism leading to catastrophe

Hagen-Poiseuille's law:


$$\frac{V}{t} = \frac{R^4 \pi \Delta p}{8\eta \Delta x}$$

- Flow intensity, hence the delivered oxygen quantity, may be **drastically reduced** in certain pathological conditions:
- constriction of blood vessels (e.g., diabetes, B rger's disease)
  - change in blood viscosity (e.g., fever, anaemia)
  - Reduction of vessel diameter by half leads to a reduction of volumetric flow by 1/16!

# Medical significance of fluid flow laws


regulation of the intensity of blood flow  
(Hagen-Poiseuille's law)

$$I_V = \frac{V}{t} = \frac{R^4 \pi \Delta p}{8\eta \Delta x}$$



Physiological regulation of the blood flow depending on the needs of tissues/organs



# Flow parameters in the circulation



# Flow conditions in the arterial system

pulsatile flow

elastic arterial wall



# Viscosity of blood

<b>55-60% of body mass is water</b> 42 kg (70 kg body mass)		
2/3 intracellular 28 kg	1/3 extracellular 14 kg	
	1/3 plasma 4-5 kg	2/3 intersticium 9-10 kg

**Blood:** Average volume: 5 l  
Average viscosity: 5 mPas  
Average density: 1.05 g/cm<sup>3</sup>  
Composition: 40-45 % corpuscular, 55-60 % plasma

# Viscosity of blood

**I. Hematocrit (htc,  $\phi$ ):**


$$htc = \frac{V_{cells}}{V_{total}}$$

Normal range: 0.4-0.5.

Viscosity of blood as suspension  
(in the physiologically relevant htc range):

$$\lg \eta_s = A + B\phi$$

$\eta_s$ =suspension viscosity  
A, B=empirical constants



# Viscosity of blood

## 2. Plasma viscosity


- Depends on plasma proteins.
- In *paraproteinaemias* (e.g. myeloma multiplex or plasmocytoma) the concentration of immunoglobulins is high, leading to increased viscosity.

<b>Plasma protein</b>	<b>Normal concentration</b>	<b>% ratio</b>	<b>Function</b>
Albumin	35-50 g/l	55%	maintenance of colloind osmotic pressure, transport
Globulins	20-25 g/l	38%	Part of the immune system
Fibrinogen	2-4.5 g/l	7%	Blood coagulation


# Viscosity of blood

## **3. Plasticity of red blood cells**

- 65% suspension of blood-cell-size particles is rock hard.
- By contrast, a 95% blood suspension is fluid, with viscosity of  $\sim 20$  mPas!
- Deformation of red blood cells: droplet, parachute, arrowhead shapes.



Disk-shaped cells with 7-11  $\mu\text{m}$  diameter



# Viscosity of blood


## 4. Aggregation of red blood cells

- Stack or rouleaux formation.
- More pronounced at low flow rates





Rouleaux (stack)

## 5. Flow rate, velocity gradient




# Viscosity of blood


## 6. Blood vessel diameter




- With a decrease of vessel diameter, the anomalous (non-newtonian) behavior of blood becomes more pronounced.
- *Axial migration*: the red blood cells line up in the axis of the vessel (Bernoulli's law). In the axis the velocity gradient decreases, and near the vessel wall it increases. Increase in velocity gradient decreases apparent viscosity (Fåhræus-Lindquist effect).




# Adaptation of RBC due to deformability




- Individual X at rest
- Individual X after 10 km running
- ▲ Individual X after a maximal treadmill test of 15'
- ▼ Individual X after a maximal cycling test of 15'




# Viscosity of blood



**Schematic diagram of capillary formation in cold-blooded animals**



**Schematic diagram of capillary formation in mammals**



Related chapters:

*Damjanovich, Fidy, Szöllösi: Medical biophysics*

III./1.

1.1

1.2

1.3

1.4

1.5

*Practicals: Flow*